

अनिवार्य आवश्यकताएँ

संख्या : TEC13292108

Essential Requirements

ER No. : TEC13292108

G3 Fax Machine

© टीईसी, २०२१
© TEC, 2021

MTCTE के तहत जारी:

Issued under MTCTE by:

दूरसंचार अभियांत्रिकी केंद्र

भारत सरकार

खुर्शीद लाल भवन, जनपथ, नई दिल्ली - 110001, भारत

Telecommunication Engineering Centre

Government of India

Khurshid Lal Bhawan, Janpath, New Delhi-110001, INDIA

Essential Requirements for:

G3 Fax Machine

Certification Scheme: **SCS**

Product Fee Group: **A**

This ER covers standalone G3 Fax Machine

Note: Annexures referred to in this ER are Annexures as mentioned in "Annexures to ERs" No. TEC/SD/DD/TCP-222/02/June19 as updated from time to time and available on MTCTE portal.

This product has the following variants:

1. FAX machine with handset
2. FAX machine without handset

1. Variant 1 : FAX machine with handset

1.1 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
1.1.1	Acoustic Shock Absorption	P.360. Annex-D
1.1.2	Conducted And Radiated Emission - Class B	TEC EMI EMC Standard CISPR 22/32 EN55022/32. Annex-B
1.1.3	Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard EN/IEC:61000-4-11. Annex-B
1.1.4	Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
1.1.5	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2. Annex-B
1.1.6	Immunity to Fast Transients (Burst)	TEC EMI EMC Standard EN/IEC:61000-4-4. Annex-B

1.1.7	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
1.1.8	Immunity to RF Field Induced Conducted Disturbance	TEC EMI EMC Standard EN/IEC:61000-4-6. Annex-B
1.1.9	Immunity to Surges	TEC EMI EMC Standard EN/IEC:61000-4-5. Annex-B
1.1.10	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1
1.1.11	Over Voltage and over Current Protection on 2W	K.21. Annex-D
1.1.12	Receiver Sensitivity for FAX	T.4. Annex-D
1.1.13	Transmit Power Fax Machine	T.4. Annex-D

1.2 Interface 1 : 2 Wire

S.No.	Parameter Name	Standard Name
1.2.1	Idle State Current for 2 wire Int	ETSI EN 300 001 ETSI TBR-21 Cl. 4.4.1. Annex-D
1.2.2	Insulation Test for 2 wire Int	ETSI EN 300 001. Annex-D
1.2.3	Longitudinal Conversion Loss for 2W Int	Q.552 Cl. 2.2.2. Annex-D
1.2.4	Maximum Loop Current for 2W Int	ETSI EN 300 001 ETSI TBR-21 Cl.4.4.3. Annex-D
1.2.5	Return Loss for 2W Int	Q.552 Cl. 2.2.1.2. Annex-D

2. Variant 2 : FAX machine without handset

2.1 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
2.1.1	Conducted And Radiated Emission - Class B	TEC EMI EMC Standard CISPR 22/32 EN55022/32. Annex-B
2.1.2	Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard EN/IEC:61000-4-11. Annex-B
2.1.3	Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
2.1.4	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2.

		Annex-B
2.1.5	Immunity to Fast Transients (Burst)	TEC EMI EMC Standard EN/IEC:61000-4-4. Annex-B
2.1.6	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
2.1.7	Immunity to RF Field Induced Conducted Disturbance	TEC EMI EMC Standard EN/IEC:61000-4-6. Annex-B
2.1.8	Immunity to Surges	TEC EMI EMC Standard EN/IEC:61000-4-5. Annex-B
2.1.9	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1
2.1.10	Over Voltage and over Current Protection on 2W	K.21. Annex-D
2.1.11	Receiver Sensitivity for FAX	T.4. Annex-D
2.1.12	Transmit Power Fax Machine	T.4. Annex-D

2.2 Interface 1 : 2 Wire

S.No.	Parameter Name	Standard Name
2.2.1	Idle State Current for 2 wire Int	ETSI EN 300 001 ETSI TBR-21 Cl. 4.4.1. Annex-D
2.2.2	Insulation Test for 2 wire Int	ETSI EN 300 001. Annex-D
2.2.3	Longitudinal Conversion Loss for 2W Int	Q.552 Cl. 2.2.2. Annex-D
2.2.4	Maximum Loop Current for 2W Int	ETSI EN 300 001 ETSI TBR-21 Cl.4.4.3. Annex-D
2.2.5	Return Loss for 2W Int	Q.552 Cl. 2.2.1.2. Annex-D