

अनिवार्य आवश्यकताएँ

संख्या : TEC67472003

Essential Requirements

ER No. : TEC67472003

IP Terminal

© टीईसी, २०२०
© TEC, 2020

MTCTE के तहत जारी:

Issued under MTCTE by:

दूरसंचार अभियांत्रिकी केंद्र

भारत सरकार

खुर्शीद लाल भवन, जनपथ, नई दिल्ली - 110001, भारत

Telecommunication Engineering Centre

Government of India

Khurshid Lal Bhawan, Janpath, New Delhi-110001, INDIA

Essential Requirements for:

IP Terminal

Certification Scheme: **GCS**

Product Fee Group: **B**

This ER covers all types of SIP Terminals

Note: Annexures referred to in this ER are Annexures as mentioned in "Annexures to ERs" No. TEC/SD/DD/TCP-222/02/June19 as updated from time to time and available on MTCTE portal.

This product has the following variants:

1. SIP Terminal

1. Variant 1 : SIP Terminal

1.1 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
1.1.1	Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
1.1.2	Conducted And Radiated Emission - Class B	TEC EMI EMC Standard CISPR 22/32 EN55022/32. Annex-B
1.1.3	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2. Annex-B
1.1.4	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
1.1.5	Immunity to Fast Transients (Burst)	TEC EMI EMC Standard EN/IEC:61000-4-4. Annex-B
1.1.6	Immunity to Surges	TEC EMI EMC Standard EN/IEC:61000-4-5. Annex-B
1.1.7	Immunity to RF Field Induced Conducted	TEC EMI EMC Standard EN/IEC:61000-4-6.

	Disturbance	Annex-B
1.1.8	Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard EN/IEC:61000-4-11. Annex-B
1.1.9	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1
1.1.10	IPV6 Header Parameters	RFC 2460 or 8200. Annex-P7
1.1.11	Dual IP Layer Operation RFC 4213 - Address	RFC 4213 Cl. 2.1. Annex-P6
1.1.12	Dual IP Layer Operation RFC 4213 - DNS	RFC 4213 Cl. 2.1. Annex-P6
1.1.13	RTCP Parameters RFC 3551 Set-A	RFC 3551. Annex-P3
1.1.14	RTP Parameters RFC 3550 Set-A	RFC 3550. Annex-P2
1.1.15	SIP Parameters Set-A	RFC 3261. Annex-P1
1.1.16	TCP Parameters	RFC 793. Annex-P4

1.2 Interface 1 : 1 G Optical Ethernet

S.No.	Parameter Name	Standard Name
1.2.1	Average Launch power for 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H
1.2.2	Receiver Sensitivity 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H
1.2.3	Wavelength for 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H

1.3 Interface 2 : 10 100 1000 BASE-T Ethernet

S.No.	Parameter Name	Standard Name
1.3.1	Link Speed and Autonegotiation Test GE	IEEE 802.3. Annex-H

1.4 Interface 3 : 10 100 BASE-T Ethernet

S.No.	Parameter Name	Standard Name
1.4.1	Link Speed and Autonegotiation Test FE	IEEE 802.3 Annex-H